	CERTIFICATE OF CA Ricardo Energy and Environment, Gemini Bu Didcot, Oxfordshire OX11 OQR. Tele	ilding, Fermi Avenue Harwell,	RICARDO
			Page 1 of 3
Approved Signatories:		 S. Eaton D Hector N Rand B Davies 	□ B Stacey □ S Stratton □ S Telfer ☑ S Gray
Signed:	Here Co		
Date of issue:	09 May 19		
Certificate Number:	4517		
Customer Name and Add	dress:	Scottish Government Water, Air, Soils and Floodi Environmental Quality Dire Scottish Government Victoria Quay Edinburgh EH6 6QQ	-
Description:		Calibration factors for th West Dunbartonshire Co	e air monitoring station(s) at uncil
Ricardo Energy & Enviro	nment ID:	ED61598/4517	
level of confidence of app requirements. This certificate is issued in Service. It provides tracea National Physical Laborat	ncertainties are based on a standard uncertainty roximately 95% The uncertainty evaluation has accordance with the laboratory accreditation r bility of measurement to the SI system of units a ory or other recognised national metrology insti e prior written approval of the issuing laborator	been carried out in accordance with equirements of the United Kingdom and/or to units of measurement real tutes. This certificate may not be rep	Accreditation sed at the
Ricardo Energy & Environm Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR Tel: +44 (0)1235 753 000	eent Registered off Shoreham Tecl Shoreham-by-2 West Sussex BN43 5FG Registered in 08229264 VAT Registrat GB 212 8365 2	nnical Centre Sea England No. ion No.	
			ee.ricardo.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	09 May 19	
Certificate Number:	4517	
Ricardo Energy & Environment ID:	ED61598/4517	

West Dunbartonshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
West Dunbartonshire Clydebank	03-Jul-18	NOx	501004	-55.3	2.5	1.0013	3.50	95.5
		NO		-55.9	2.5	1.0100	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
West Dunbartonshire Clydebank	03-Jul-18	6250			4.95	2.2		2.2

PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
West Dunbartonshire Clydebank	03-Jul-18	6250			4.95	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

		Page 3
Date of issue:	09 May 19	
Certificate Number:	4517	
Ricardo Energy & Environment ID:	ED61598/4517	

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 2 The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com